



SECTION B-B

VIEW A
NON SCALE

- NOTES:**
- 1- ALL DIMENSIONS ARE IN mm.
 - 2- ALL TOLERANCES ARE ACCORDING TO DIN 7186-m UNLESS OTHERWISE SPECIFIED.
 - 3- BELT EP315/3, 5+2 WROD.
 - 4- USE SHIMS FOR SUPPORTS ADJUSTING ONLY WHEN NECESSARY.

REF. TO DWG. NO.	DESCRIPTION	QTY.	REF. TO DWG. NO.	DESCRIPTION	QTY.	REF. TO DWG. NO.	DESCRIPTION	QTY.
21	40 SPRING LOCK WASHER A14		20	NUT M14		19	BOLT M14x40	
18	BELT-25mm		17	GEAR MOTOR 7.5kW 37 RPM WITH BREAK OR BACK STOP		16	PULL CORD SYSTEM	
15	FRAME TYPE "C"		14	FRAME TYPE "B"		13	FRAME TYPE "A"	
12	SUPPORT TYPE "A"		11	MISPLUGGING SWITCH DEVICE		10	INTERNAL SCOPER	
9	RETURN ROLLER		8	CARRIER ROLLER		7	IMPACT ROLLER	
6	SELF-ALIGNER CARRIER ROLLER		5	TRANSITION ROLLER		4	STRIPBAND	
3	STRIPBAND		2	HEAD ASSEMBLY		1	TAIL ASSEMBLY	

REV.	DESCRIPTION	DESIGN	CHECK	APPR.	DATE

DESIGN	MM.Maharhoue	DESIGN STRAIG
DRAWING NO.	A-AS-U-M-9011A-140	FOR APPROVAL
SCALE	AS SHOWN	UNITS
REV. 01	AS SHOWN	SH. SIZE
ASSEMBLY BELT 11m A		MILLIMETER
		A2